

**VILLAGE OF LAWTON  
BUILDING PERMIT FEES**

***Please note : All Fee calculations are rounded to the nearest dollar amount. Payment for the permit is due at the time of application***

New Home: (Includes all double-wide or modular homes on private property)

Add in the square footage of attached garage and, if finished at time of construction, the square footage of finished basement. No charge for porches or decks when obtaining a new building permit for a home.

<u>Square Feet</u>	<u>Per Sq. ft.</u>
1000 - 2000	\$0.25
2001 - 3000	\$0.21
3001 & Over	\$0.22

<b>Multiple Dwellings</b> .....	\$0.20 / sq. ft.
<b>Pole Barn</b> .....	\$100 minimum..... \$0.22 / sq. ft.
<b>Structures under 200 sq. feet</b> (shed and barns).....	No charge
<b>Detached garage</b> .....	\$100 minimum..... \$0.22 / sq. ft.
<b>Remodel / Addition</b> .....	\$150 minimum..... \$0.25 / sq. ft.
<i>(i.e. Attached garage after home built, carports, or siding w/structural changes</i>	
<b>Re-roof w/new decking (OSB) structure changes</b> .....	\$100.00 - all sizes
<b>Re-roof or siding w/ NO structure changes</b> .....	\$ 50.00 - all sizes
<b>Deck</b> .....	\$125.00 - all sizes
<b>Porch</b> .....	\$125.00 - all sizes
<b>Deck &amp; Porch</b> .....	\$175.00 - all sizes
<b>Fence</b> .....	No charge
<b>In-ground Pool</b> .....	\$100 minimum..... \$0.25 / sq. ft.

\*\* A \$300 permit bond is payable at the time of issuance of a permit for a swimming pool and will be refunded at the time of final inspection. A final inspection must be requested within a one year time period from date of issuance, otherwise the bond will be forfeited.

<b>Above-ground pool</b> .....	\$50.00 - all sizes
<b>Demolition</b> .....	\$
<b>Signs</b> .....	\$100.00 - a sizes
<b>Solar</b> .....	\$100.00

**Commercial / Industrial** (incl. additions) ..... \$150 minimum ..... \$0.50 / sq. ft.

\* Commercial plan review will be billed at the State of Michigan Bureau of Construction Code Plan Review fee schedule based on use Group and type of construction and square footage.

Schedule is available on the State web site or copies are available at the Township Office.

\*\* Commercial multi-unit building interior finish will be charged per inspection (\$50) after an original permit is obtained for entire building.

<b>Re-inspection Fee</b> .....	\$50.00 / inspection
<b>Additional inspections</b> .....	\$50.00 / inspection

**Building Fines**

Building without securing a permit before construction begins:

*Residential* ..... Half of the original permit amount

*Commercial* ..... Half of the original permit amount

**ALL EXPIRED PERMITS:** Renewal Fee ..... \$50.00 for each inspection needed

VILLAGE OF LAWTON  
**BUILDING PERMIT APPLICATION**

\*\*\*\*\*PAYMENT FOR THE PERMIT IS DUE AT THE TIME OF APPLICATION\*\*\*\*\*

The holder of the general contractor license or a direct representative of the company must apply and make payment for permits, not the owner of the home or business. (Property owners acting as their own general contractor will meet the same application requirements as the licensed general contractors.)

Submit completed building permit application to the Village of Lawton office during regular business hours;

PO BOX 367

125 S. MAIN STREET

LAWTON, MI 49065

269-624-6407

Applications are approved by appointment with the Inspector. Please call 269-207-7271 to schedule

A building permit is valid for 6 months from the date of application. Prior to expiration of the permit, you must notify the building inspector if you need an extension of that permit (an additional 6 months is no charge). After 12 months, you will need to reapply and pay for a new permit. The renewal fee is half of the original amount.

**New Homes**

We will not accept any building permit applications without the following:

1. One set of blue-prints/detailed drawings showing the floor plan, room dimensions, window sizes, special features, front and side elevations, foundation plans, and a cross section of the foundation wall and exterior walls. (An architect's seal is required for all commercial and or industrial buildings.)
2. Correspondence from Miss Dig and/or Public Works Department for Water / Sewer hook-up.
3. A complete application for the permit. This information is not limited to, but must include, the street address of the proposed building; the property ID number, the name, mailing address and phone number of the deed holder; the name, federal ID number; workman's comp insurance carrier name, liability insurance carrier of all contractors; the proposed building cost.
4. A site plan drawing (enclosed with the building permit application packet) showing existing and proposed buildings.
5. A copy of the deed to the property if a conveyance of ownership is recent (within 45 days prior to submittal of this application).

### **Additions, Garages, Pole Barns, Pools, Decks, etc.**

Detailed drawings are required for all additions and/or major structural changes, (i.e. foundation size and depth, the size of addition, type and quantity of floor joists, if steel beam or blue-laminated supports, wall size, and if trusses or stick built roofing.

### **Pole Barns and Other Detached Structures**

In order for the building inspector to issue a permit for the pole barns or other detached structures, you must follow these requirements:

- Post locations and cross-sections showing post size, footing, support boards, elevation cross sections, etc.
- Elevations are not required, but all other building provisions apply.

### **Inspector Information**

The Building Inspector, Ron Verleger, processes applications by appointment and is available during regular business hours. You can reach him by call 269-207-7271 or the Village 269-624-6407.

### **Inspection Requests**

The Building Inspector will process building inspections for footings, foundations, rough-ins, insulation, finals, and occupancies within a 24 hour period from the time you request the inspection. Before requesting a rough-in or final from the inspector, please make sure that all other inspections (i.e. plumbing, electrical, mechanical) have been completed. Occupancies will not be processed until all fees have been paid.

**BUILDING PERMIT APPLICATION**  
for  
**LAWTON VILLAGE**

Job Address \_\_\_\_\_ City \_\_\_\_\_ Zip \_\_\_\_\_  
Parcel ID No: 80-45-\_\_\_\_\_  
Application Date: \_\_\_\_/\_\_\_\_/\_\_\_\_

<b>Office Use Only</b>				
Permit # Village _____	Permit Fee: \$ _____	Amount Paid: \$ _____	Issue Date ____/____/____	
Cash _____		Check # _____		
Driveway Permit # _____	Sewer Permit # _____	Well Permit # _____		

Property Owner Name (____)	Address _____	City _____	State _____	Zip _____
Home Phone _____	Work Phone _____			
Architect/Engineer (____)	Address _____	City _____	State _____	Zip _____
Phone _____	License No. _____	License Expiration Date _____		
Federal ID No. / Social Security No. _____		Workman's Comp. Insurance Carrier _____		

**TYPE OF PROJECT**

New                       Repair                       Foundation Only                       Mobile Home Set Up  
 Addition                       Manufactured Home                       Relocation                       Special Inspection  
 Alteration/Remodel

**Residential**

Single Family                       Two Family or More ( No. of Units \_\_\_\_\_ )  
  
 Attached Garage                       Detached Garage                       Pole Barn                       Deck  
 Porch                       In-Ground Pool                       Above Ground Pool                       Remodel/ Addition

**Non-Residential**

Industrial                       Store/Mercantile                       Office/Bank/Professional                       Service Station  
 Church/Religion                       Hospital/Institutional                       School/Library/Education                       Parking Garage  
 Amusement                       Public Utility                       Tank /Tower                       Hotel/Motel  
(No. of Units \_\_\_\_\_)

Describe in detail the proposed use of building, (e.g. food processing plant, machine shop, elementary school, rental office, etc.)

---



---



---

**CHARACTERISTICS of BUILDING**

**Principal Type of Frame**

Masonry/Wall Bearing \_\_\_\_\_ Wood \_\_\_\_\_ Structural Steel \_\_\_\_\_ Reinforced Concrete \_\_\_\_\_ Other \_\_\_\_\_

**Principal Type of Heating**

Gas \_\_\_\_\_ Oil \_\_\_\_\_ Electric \_\_\_\_\_ Coal \_\_\_\_\_ Other \_\_\_\_\_

**Type of Sewage Disposal**

Public or Private Company \_\_\_\_\_ Septic System \_\_\_\_\_

**Type of Water Supply**

Public or Private Company \_\_\_\_\_ Private Well or Cistern \_\_\_\_\_

**Mechanical**

Air Conditioning: Yes \_\_\_\_\_ No \_\_\_\_\_ Fire Suppression: Yes \_\_\_\_\_ No \_\_\_\_\_

**Number of Stories**

Garage: Attached \_\_\_\_\_ Detached \_\_\_\_\_ Finished \_\_\_\_\_ (if attached or finished, include sq footage in total, if detached a separate building permit application is necessary)

**Type of Foundation**

Basement \_\_\_\_\_ Crawl Space \_\_\_\_\_ Slab \_\_\_\_\_  
Basement being finished at time of Construction: Yes \_\_\_\_\_ No \_\_\_\_\_ (if yes include square footage in total)

**Soil Erosion Permit**

Is the property located within 500 ft. of any type of water (i.e. stream, river, lake) Yes \_\_\_\_\_ No \_\_\_\_\_  
Are you removing more than one acre of topsoil? Yes \_\_\_\_\_ No \_\_\_\_\_

\*\* If Yes, please contact Van Buren County 269-657-8241. A soil erosion permit is necessary before a building permit can be issued.

**Agricultural Use**

Is this project for agricultural purposes? Yes \_\_\_\_\_ No \_\_\_\_\_

\*\*If yes, a written letter must be submitted with the Building Permit Application indicating its use as it applies to the Agricultural Exemption for Building Permit. Your permit will be treated as a fee based permit if a letter is not provided.

Total Estimated Cost of Construction: \$ \_\_\_\_\_

**Square Footage of Building Project**

**Living Area:**

1<sup>st</sup> Floor \_\_\_\_\_ 2<sup>nd</sup> Floor \_\_\_\_\_ 3<sup>rd</sup> -10<sup>th</sup> Floor \_\_\_\_\_ 11<sup>th</sup> Floor & Above \_\_\_\_\_

Attached Garage: \_\_\_\_\_ Finished Basement: \_\_\_\_\_

Total Square Footage \_\_\_\_\_

X \_\_\_\_\_ /sq. ft. (see Building Permit Fees\_

Deck/ Porch Fee + \_\_\_\_\_ (Size does not vary cost)

Total Cost of Permit: \$ \_\_\_\_\_ Rounded to the nearest dollar.

Section 23 a of the State Construction Code Act of 1972, PA 230, MCL 125.1523a, prohibits a person from conspiring to circumvent the licensing requirements of this state relating to persons who are to perform work on a residential building or structure. Violators of Section 23a are subject to civil fines.

CONTRACTOR'S/AGENT'S AFFIDAVIT: I hereby certify that the proposed work is authorized by the owner of record and I have been authorized by the owner to make this application as his/her authorized agent, and we agree to conform to all applicable laws of the State of Michigan. All information submitted on this application is accurate to the best of my knowledge.

Signed: \_\_\_\_\_ - Date: \_\_\_\_\_

HOMEOWNERS AFFIDAVIT: I hereby certify that the work described on this permit application shall be installed by me in my own single family dwelling in which I am living or about to occupy. All work shall be installed in accordance with the local code and shall not be enclosed, covered up, or put into operation until it has been inspected and approved by the inspector. I will cooperate with the inspector and assume the responsibility to arrange for necessary inspections.

Signed \_\_\_\_\_ - Date: \_\_\_\_\_

**THE APPLICANT MUST COMPLETE THIS FORM**

You must illustrate on this grid the property dimensions and the location of the proposed house and/or outbuilding. Also, you must indicate all existing structures, show all property setbacks, including the centerline of the road to the house and the side and rear setbacks.

A large grid for drawing property dimensions and setbacks. The grid is composed of 25 columns and 25 rows of small squares, providing a scale for the applicant to draw the property boundaries, setbacks, and the location of any proposed structures.

Antwerp Township

PERMIT # \_\_\_\_\_

PARCEL # \_\_\_\_\_

OWNER'S NAME \_\_\_\_\_

EVE WIDTH \_\_\_\_\_


JOB ADDRESS \_\_\_\_\_

SHINGLES/SF \_\_\_\_\_

ROOF PITCH \_\_\_\_\_

TRUSS DIAGRAM  
REQ. OR  
RAFTER SIZE

ROOF SHEATHING \_\_\_\_\_



SIZE OF HEADER \_\_\_\_\_

HEIGHT \_\_\_\_\_

WIDTH \_\_\_\_\_

LENGTH \_\_\_\_\_

GRADE

CONCRETE FLOOR THICKNESS \_\_\_\_\_

42"  
MIN

TAMPED SAND BASE \_\_\_\_\_

FOOTING \_\_\_\_\_

TREATED PLATE \_\_\_\_\_

POURED IN PLACE FOOTER (MIN 16")

Sketch by Apex IV Windows™

## MICHIGAN RESIDENTIAL CODES

The following are excerpts of the Michigan Residential Codes for your information. ***Please deep these pages for your references. It is necessary to return these with your permit application.***

### **SECTION R1-6/CONSTRUCTION DOCUMENTS**

#### **R106.1.1 Information on Construction Documents (Page 4)**

Construction documents shall be drawn upon suitable material. Electronic media documents are permitted to be submitted when approved by the building official. Construction documents shall be sufficient clarity to indicate the location, nature, and extent of the work proposed and show in detail that it will conform to the provisions of this code and relevant laws, ordinances, rules and regulations, as determined by the building official.

#### **R106.1.2 Manufacturer's Installation Instructions (Page 4)**

Manufacturer's installation instructions, as required by this code, shall be available on the job site at the time of inspection.

#### **R106.2 Site Plan (Page 5)**

The construction documents submitted with the application for permit shall be accompanied by a site plan showing the site and location of new construction and existing structures on the site and distances from lot lines. In the case of demolition, the site plan shall show construction to be demolished and the location and size of existing structures and construction that are to remain on the site or plot.

### **SECTION R403/FOOTINGS**

#### **R403.1.6 Foundation Anchorage (Page 59)**

When braced wall panels are supported directly on continuous foundations, the wall wood sill plate or cold-formed steel bottom track shall be anchored to the foundation in accordance with this section. In Seismic Design Categories D1 and D2, the additional anchorage requirements of Section R602.11.1 shall apply for wood framing. In Seismic Design Categories D1 and D2 where continuous wood foundations in accordance with Section 404.2 are used, the force transfer shall have a capacity equal to or greater than the connections required by R602.11.1 or the braced wall panel shall be connected to the wood foundations in accordance with the braced wall panel-to-floor fastening requirements of Table R602.3(1).

The Wood sold plate at exterior walls on monolithic slabs and wood sill plate shall be anchored to the foundation with anchor bolts spaced a maximum of 6 feet (1829 mm) on center. Anchor bolts shall also be located within 12 inches (305 mm) from the end of each plate section. In seismic Design Categories D1 and D2, anchor bolts shall also be spaced at 6 feet (1829 mm) on center and located within 12 inches (305mm) from the ends of each section at interior braces wall lines when required by Section R602.10.9 to be supported on a continuous foundation. Bolts shall be at least ½ inch (12.7 mm) in diameter and shall extend a minimum of 7 inches (178 mm) into masonry or concrete. Interior bearing wall sole plates on monolithic slab foundations shall be positively anchored with approved fasteners. A nut and washer shall be tightened on each bolt to the plate. Sills and sole plates shall be protected against decay and termites where required by Sections R322 and R323. Cold formed steel framing systems shall be fastened to the wood sill plates or anchored directly to the foundation as required in Section R505.3.1 or R603.1.1.

**Exception: Foundation anchor straps, spaced as required to provide equivalent anchorage to ½ inch diameter (12.7mm) anchor bolts.**



## **SECTION R401 / FOUNDATIONS**

### **R401.4 Soil Tests (Page 57)**

In areas likely to have expansive, compressible, shifting, or other unknown soil characteristics, the building official shall determine whether to require a soil test to determine the soil's characteristics at a particular location. This test shall be made by an approved agency using an approved method.

## **SECTION R601 / WALL CONSTRUCTION**

### **R602.6 Drilling and Notching – Studs (Page 112)**

Any stud in an exterior wall or bearing partition may be cut or notched to a depth not exceeding 15% of its width. Studs in nonbearing partitions may be notched to a depth not to exceed 40% of a single stud width. Any stud may be bored or drilled, provided that the diameter of the resulting hole is no greater than 40% of the stud width, the edge of the hole is no closer than 5/8 inch (15.9mm) to the edge of the stud, and the hole is not located in the same section as a cut or notch. See Figures R602.6 (1) and R602.6 (2).

EXCEPTIONS: 1) A stud may be bored to a diameter not exceeding 60% of its width, provided that such studs located in exterior wall or bearing partitions are doubled and that not more than two successive studs are bored. 2) Approved stud shoes may be used when installed in accordance with the manufacturer's recommendation.

#### **R602.6.1 Drilling & Notching of Top Plate (Page 112)**

When piping or ductwork is placed in or partly in an exterior wall or interior, braced or load-bearing wall, necessitating a cutting of the top plate by more than 50% of its width, a galvanized metal tie not less than 0.054 inch thick (1.37mm, 16 gauge) and 1.5 inches (38mm) wide shall be fastened to each plate across and to each side of the opening with not less than six 16d nails (see Figure R602.6.1).

EXCEPTION: When the entire side of the wall with the notch or cut is covered by wood structural panel sheathing.

## **SECTION R314 / STAIRWAYS**

### **R314.1 Width (Page 47)**

Stairways shall not be less than 36 inches (914mm) in clear width at all points above the permitted handrail height and below the required headroom height. Handrails shall not project more than 4.5 inches (114mm) on either side of the stairway and the minimum clear width of the stairway at and below the handrail height, including treads and landings, shall not be less than 31.5 inches (787mm) where handrail is installed on one side and 27 inches (698mm) where handrails are provided on both sides.

EXCEPTION: The width of spiral stairways shall be in accordance with Section R314.5

### **R314.2 Treads and Risers (Page 47)**

The maximum riser height shall be 8-1/4 inches (210mm) and the minimum tread depth shall be 9 inches (229mm). The riser height shall be measured vertically between leading edges of the adjacent treads. The tread depth shall be measured horizontally between the vertical planes of the foremost projection of adjacent treads and at a right angle to the tread's leading edge. The walking surface of treads and landings of a stairway shall be sloped no steeper than one unit vertical in 48 units horizontal (2% slope). The greatest riser height within any flight of stairs

shall not exceed the smallest by more than 3/8 inch (9.5mm). The greatest tread depth within any flight of stairs shall not exceed the smallest by more than 3/8 inch (9.5mm).

## **SECTION R310 / EMERGENCY ESCAPE AND RESCUE OPENINGS**

### **R310.1 Emergency Escape and Rescue Required (Page 46)**

Basements and habitable space and every sleeping room shall have at least one openable emergency escape and rescue. Where openings are provided as a means of escape and rescue they shall have a sill height of not more than 44 inches (1118mm) above the floor. Where a door opening having a threshold below the adjacent ground elevation serves as an emergency escape and rescue opening and is provided with a bulkhead enclosure, the bulkhead enclosure shall comply with Section R310.3. The net clear opening dimensions required by this section shall be obtained by the normal operation of the window or door opening from the inside. Escape and rescue window openings with a finished sill height below the adjacent ground elevation shall be provided with a window well in accordance with R310.2.

#### **R310.1.1 Minimum Opening Area (Page 46)**

All emergency escape and rescue opening shall have a minimum net clear opening of 5.7 square feet (0.530 m<sup>2</sup>).

EXCEPTION: Grade floor opening shall have a minimum net clear opening of 5 square feet (0.465 m<sup>2</sup>).

#### **R310.1.2 Minimum Opening Height (Page 46)**

The minimum net clear opening width shall be 24 inches (610mm).

#### **R310.1.3 Minimum Opening Width (Page 46)**

The minimum net clear opening width shall be 20 inches (508mm).

#### **R310.1.4 Operational Constraints (Page 46)**

Emergency escape and rescue openings shall be operational from the inside of the room without the use of keys or tools.

## **SECTION R311 / EXITS**

### **R311.4 Hallways**

The minimum width of a hallway shall be not less than 3 feet (914mm).

## **SECTION R806 / ROOF VENTILATION**

### **R806.1 f Ventilation Required (Page 242)**

Enclosed attics and enclosed rafter spaces formed where ceilings are applied directly to the underside of roof rafters shall have cross ventilation for each separate space by ventilating openings protected against the entrance of rain or snow. Ventilated openings shall be provided with corrosion-resistant wire mesh, with 1/8 inch (3.2mm) to 1/4 inch (6.35mm) maximum openings.

### **R806.2 Minimum Area (Page 242)**

The total net free-ventilating area shall not be less than 1-150 of the area of the space ventilated except that the total area is permitted to be reduced to 1-to 300, provided at least 50% and not more than 80% of the required ventilating area is provided by ventilators located in the upper portion of the space to be ventilated at least 3 feet (914mm) above eave or cornice vents with the balance of the required ventilation provided by eave or cornice

vents. As an alternative, the net free cross-ventilation area may be reduced to 1 to 300 when a vapor barrier having a transmission rate not exceeding 1 perm (57.4 mg/s.m<sup>2</sup>.Pa) is installed on the warm side of the ceiling.

**R806.3 Vent Clearance (Page 242)**

Where eave or cornice vents are installed, insulation shall not block the free flow of air. A minimum of a 1-inch (25.4mm) space shall be provided between the insulation and the roof sheathing at the location of the vent.

**R602.8 Fireblocking Required (Page 114)**

Fireblocking shall be provided to cut off all concealed draft openings (both vertical and horizontal) and to form an effective fire barrier between stories, be provided in wood-frame construction in the following locations:

1. In concealed spaces of stud walls and partitions, including furred spaces, at the ceiling and floor level and at 10-foot (3048mm) intervals both vertical and horizontal. Batts or blankets or mineral or glass fiber or other approved nonrigid material shall be allowed as fireblocking in walls constructed using parallel rows of studs or staggered studs.
2. At all interconnections between concealed vertical and horizontal spaces such as occur at soffits, drop ceilings, and cove ceilings.
3. In concealed spaces between stair stringers at the top and bottom of the run. Enclosed spaces under stairs shall comply with Section R314.8.
4. At openings around vents, pipes, and ducts at ceiling and floor level, with an approved material to resist the free passage of flame and products of combustion.
5. For the fireblocking of chimneys and fireplaces, see Section R1001.16.
6. Fireblocking of cornices of a two-family dwelling is required at the line of dwelling unit separation.

**SECTION R110 / CERTIFICATE OF OCCUPANCY**

**R110.1 Use and Occupancy (Page 6)**

A building or structure shall not be used or occupied, and a change in the existing occupancy classification of a building or structure or portion thereof shall not be made until a certificate of occupancy has been issued in accordance with Section 13 or the act.